

Zurich
Instruments

SHFQC+ 8.5 GHz Qubit Controller


Qubit control and readout of up to 6 qubits
in a single instrument

Product Leaflet

Release date: 29.02.2024

Key Features

- 2, 4, or 6 signal generator channels, 1 quantum analyzer channel
- Operation at up to 8.5 GHz with 1 GHz analysis bandwidth and free of mixer calibration
- Low phase noise, low spurious tones and high output power for fast, high-fidelity gates
- Real-time signal processing chain with matched filters and multi-state discrimination
- Ultrafast instrument-internal feedback
- Controlled through LabOne, LabOne Q, or APIs for Python



Introduction

The SHFQC+ Qubit Controller controls, reads out and provides fast feedback on up to 6 superconducting qubits. The signal generator channels for qubit control and quantum analyzer channel for readout are tightly linked through trigger and data distributions. The SHFQC+ comes in three possible configurations, in which either 2, 4, or 6 of the signal generator channels are enabled. Additional signal generator channels can be enabled in the field. As a result, the SHFQC+ is fully software-controlled and can be easily reconfigured.

The signal generator channels have powerful sequencers for real-time phase, frequency and timing control of waveforms, and branching based on inputs from other channels. The quantum analyzer channel and the SHFQC-16W option enable multiplexed and multi-state single-shot readout. Features such as a real-time oscilloscope, fast spectroscopy, and pulse-level sequencing improve system tune-up and measurement speeds.

As part of the Zurich Instruments Quantum Computing Control System (QCCS), the SHFQC+ benefits from intuitive operation through LabOne Q and seamlessly interfaces with other QCCS instruments.

Applications

Quantum computing applications

- Coherent control of qubits through single and multi-qubit gates
- Frequency-multiplexed readout
- Dispersive single-shot readout
- Fast qubit and resonator spectroscopy, and setup characterization
- Real-time, low-latency feedback for system-wide operations and error correction protocols
- Systems from 1 or 2 qubits to more than 100 qubits

Supported qubit types

- Superconducting qubits
- Spin qubit/superconducting resonator hybrids
- Qubits, qutrits und ququads

Other applications

- Amplifier noise characterization
- Microwave setup calibration

Highlights

High-fidelity qubit manipulation and readout

Operating over a range that extends up to 8.5 GHz, the double superheterodyne up- and down-conversion scheme of the SHFQC+ relies on filtering rather than on interference, so that it performs over a wider frequency band and with better linearity than standard IQ-mixer-based conversion approaches. In combination with synthesizers offering low phase noise and low timing jitter across the whole output frequency range, the SHFQC+ generates spurious-free and stable signals ideal for high-fidelity qubit control and readout - all available without spending time on mixer calibration.

The combination of superheterodyne frequency conversion with a linear amplification chain allows users to drive all single- and multi-qubit gates within short time intervals and free of distortion. Furthermore, the large spurious free dynamic range of the SHFQC+ also allows for more flexibility when designing the readout frequencies as sub-optimally located spurs do not need to be avoided. In summary, the integrated frequency conversion offered by the SHFQC+ ensures that qubit control and readout operations realize the full potential of a quantum processor in terms of fidelity.

Efficient workflow and resource handling

The signal generator and quantum analyzer channels of the SHFQC+ require minimal waveform and instruction memory even for complex gate sequences thanks to an efficient pulse-level sequencing approach. This approach ensures that complex tune-up and calibration routines are completed with a minimum of instrument communication overhead - even for large systems.

For example, loops and conditional branching support the implementation of active reset, while real-time phase and frequency control enable virtual Z gates. With up to 98 kSa waveform memory per channel, up to 32k sequence instructions, and a sampling rate of 2 GSa/s, the SHFQC+ provides customizable multi-channel arbitrary waveform generator (AWG) signals for qubit control and readout.

Fast readout with high fidelity

The SHFQC+ performs pulsed measurements to determine the transmission amplitude and phase of a readout resonator. Two methods help maximize the signal-to-noise ratio (SNR): pulse shaping and matched filtering. Pulse shaping with an arbitrary readout pulse generator minimizes ring-up and ring-down times. Matching the digital filters of the SHFQC+ to the transient response of the readout resonator using a 2- μ s-long weight function for each filter significantly improves the SNR compared to a simple, unweighted integration. In addition, the real-time analysis chain can discriminate up to 4 states per qubit.


Scalable system approach

By design, the SHFQC+ supports control and readout of up to 6 fixed-frequency qubits, qutrits or 5 ququads. To optimally support other qubit types, or to extend the number of qubits, the SHFQC+ can be efficiently interfaced with other instruments too. For example, the low-latency 32-bit DIO VHDCI interface enables feed-forward of the multi-qubit state to a few HDAWGs for fast active qubit reset or optimal flux-pulse control.

For systems with larger qubit counts, several SHFQC+, SHFSG+, SHFQA+ and HDAWG instruments can be combined to form a scalable QCCS. The Zurich Instruments ZSync interface links up to 56 instruments through the QHub Quantum System Hub, the instrument acting as the central controller. This enables coordinated readout and control of up to 336 fixed-frequency qubits including ultrafast feedback using only SHFQC+.


Quantum system control software

Using LabOne Q or our Python APIs, the SHFQC+ can be seamlessly integrated into new or existing setups as well as into established measurement frameworks. The one-system-control approach, combined with an extended example library, advanced data structuring and the processing functionality offered by the LabOne Data Server, ensures that the user portion of the stack remains simple and intuitive to operate and maintain.



Quantum analyzer channel analysis chain for a qutrit readout. After analog and digital down-conversion, the reference traces from the readout resonators are integrated using matched filters. Multi-state discrimination assigns the qubit states $|g\rangle$, $|e\rangle$, or $|f\rangle$ to the results and then communicates them to the signal generator channels or other instruments of the QCCS. The signals for multiplexed qutrit readout as well as the control pulses can be created with the SHFQC+.

Functional Diagram



Specifications

General

Signal Generator (SG)	2, 4, or 6 (signal outputs)
Quantum Analyzer (QA)	1 (signal input and output)
Dimensions	449 × 460 × 145 mm 17.6 × 18.1 × 5.7 inch
Weight	15 kg (33 lb)
Power supply	AC: 100 – 240 V, 50/60 Hz
External reference	10 MHz or 100 MHz
Connectors	SMA, 32-bit DIO, ZSync LAN, USB 3.0

Signal outputs

Configuration	1 per SG channel 1 for QA channel
Frequency range	DC - 8.5 GHz (SG) 0.5 GHz - 8.5 GHz (QA)
Signal bandwidth	> 1.0 GHz
Output ranges	-30 dBm to +10 dBm
Output impedance	50 Ω
D/A conversion	14-bit, 6 GSa/s
Output level accuracy	±(1 dBm of setting)

Signal inputs

Configuration	1 for QA channel
Frequency range	0.5 GHz - 8.5 GHz
Signal bandwidth	> 1.0 GHz
Input impedance	50 Ω
Input voltage noise	<2.2 nV/√Hz @ -50 dBm
Input ranges (dBm)	-50 to 10 dBm (calibrated)
D/A conversion	14-bit, 4 GSa/s

Markers and triggers

Marker outputs	2 for QA channel, 1 per SG channel
Output voltages	0 V (low), 3.3 V (high)
Output impedance	50 Ω
Trigger inputs	2 for QA channel, 1 per SG channel
Input impedance	50 Ω / 1 kΩ

Synthesizer

Analog RF Center Frequencies	1 for QA channel 3 shared by SG channels
------------------------------	---

Waveform generation

AWG cores	1 per channel
Instruction memory (SG)	32k instructions per core
Instruction memory (QA)	16k instructions
AWG sampling rate	2 GSa/s
Sequencing capability	Advanced sequencing, command table, advanced trigger control, staggered readout
Oscillators	1 per QA channel 8 per SG channel
Waveform resolution	14-bit analog
Wave memory (SG)	98 kSa per channel
Wave memory (QA)	8 × 4 kSa 16 × 4 kSa (w. SHFQC-16W)
Min. waveform length	32 Sa (only for SG channel)

Qubit measurement unit

Integration weights (Matched filters)	8 × 4 kSa 16 × 4 kSa (w. SHFQC-16W)
Multi-state discrimination	Up to 4 discriminators (qubits, qutrits, ququads)
Data logger	Memory: 2^{20} samples Averages: Max. 2^{17}
Monitor scope	Memory: 2^{17} Sa Averages: Max. 2^{16}